




### Up to 5 year warranty

European quality - Danish design.  
1100i comes with a 2 year warranty.  
Three extra year of warranty for free  
requires online product registration on  
[protectglobal.com/extra-warranty](http://protectglobal.com/extra-warranty).



### Possibility of 4 angled nozzles

1100i comes with a straight nozzle.  
However it can easily be exchanged  
with different angled nozzles with one  
or three holes straight or 30°.



### XTRA<sup>+</sup> fog fluid

Sturdy, reusable fluid container with  
XTRA<sup>+</sup> fog fluid: Extra white and dry  
fog with extended dissipation time.  
Quick and easy replacement without  
fog fluid spillage.



### Tests & approvals

The model 1100i is tested and  
approved in accordance with  
EN 50131-8 (an european standard  
for fog cannon units).  
Test certificates can be obtained on  
[protectglobal.com](http://protectglobal.com) (documentation).

# 1100i<sup>TM</sup>

Model 1100i is extremely powerful and  
fills the room very quickly. It's designed  
for protection of large spaces: office  
environments, large shops and storage  
facilities. Or even large private garages.



### Features:

- Discharges 1300 m<sup>3</sup> of fog at full speed in 60 seconds
- Flexible adjustment between 500 and 1300 m<sup>3</sup> to exactly fit the size of the room
- 100 % silent in standby mode
- Pulse function for 4 min. (effective maintenance of the fog)
- Compatible with any alarm system
- Compatible with IPCard, MultiCard and IntelliBox
- Data log memory possible with IntelliSuite
- Built-in daily, automatic battery test
- Integration with all types of alarm systems
- Prepared for 4 different angled nozzles and nozzle extension piece

### Specifications:

Fog performance, example: 60 sec. + 4 min. pulse: 1700 m <sup>3</sup>
3 time settings from 500-1300 m <sup>3</sup>
Optional pulse function (can shoot several times)
1,1 l. reusable fluid container included
Enough fluid for 4 discharges in one container
Electronic fluid measurement
Power consumption: 1350 W
Mains connection: 230V, 50 Hz
Standby consumption after heating up: 70 W (on average)
Standby consumption when heat is disabled: 5-10 W
Heating time from cold: 25 min.
Re-heating time after fog discharge: 0-8 min.
Operating temperature (min./max.): 5/80° C.
Input: 5 signals
Output: 3 signals
On/off dipswitches for setting of fog time, signals and heating
Backup of electronics and pump (2 x 12V, 1.2 Ah)
Power backup after power failure: Up to 3 hours
Built-in automatic battery testing
Optical, audible and electrical signals/indicators
Status indicator on PCB
External status indicator
Anti-sabotage, impact-resistant steel casing
Colours available: White and black
Dimensions: L: 475, W: 332, H: 174 mm
Installation weight: 16 kg

Printing errors excepted. Subject to changes to technical data.